



Per lampade ad incandescenza e scarica
For incandescent and discharge lamps

ART. 0113



ART. 0113/B



Dati tecnici

- Corpo in porcellana
- Contatti in ottone ramato
- Morsetti a bussola in ottone idonei per fili 0,5 ÷ 2,5 mm²
- Tensione nom.: 250V
- Corrente nom.: 4A
- Temperatura max del portalamпада: 210° C
- Tensione d'impulso max: 5 kV
- Categoria di tenuta all'impulso: II
- Peso: 60 gr.

Nota

Data la particolare resistenza termica del portalamпада in porcellana, esso è indicato anche per l'uso con lampade alogene a tensione di rete.

Technical data

- Porcelain body
- Coppered brass contacts
- Brass connectors terminals suitable for leads 0,5 ÷ 2,5 mm²
- Nominal voltage: 250V
- Nominal current: 4A
- Nominal highest working temperature: 210°C
- Maximum rated pulse voltage: 5 kV
- Impulse withstand category: II
- Weight: 60 gr.

Notes

In consideration of its particularly high thermal resistance, this porcelain lampholder can be used also with mains voltage halogen lamps.

Portalamпада assemblato con staffa a 90° in ferro zincato (ns. art. 050/16), completa di vite per messa a terra idonea per fili 0,5 ÷ 2,5 mm².
Peso: 65 gr.

Lampholder assembled with 90° galvanized iron camping plate (our art. 050/16), complete with earth screw, suitable for leads 0,5 ÷ 2,5 mm².
Weight: 65 gr.